



**DIRECTIVES :** 95 / 16 EC Lifts Directive  
73 / 23 / EEC Low Voltage Directive  
98 / 37 / EC Safety of Machinery Directive

**STANDARTS :** EN 60034-1 1998  
EN 60204-1 1992  
EN 81-1:2001  
EN 60204-32 : April 1999

<b>MACHINE ( SPEED - WEIGHT - POWER ) TABLE</b>						<b>Static freight</b>	<b>4.500</b>
<b>GEAR RATIO</b>	<b>MOTOR POWER</b>	<b>CARRYING FREIGHT</b>	<b>CABINET SPEED</b>	<b>ROPE</b>	<b>SHEAVE/ PITCH</b>	<b>WEIGHT</b>	
<b>Z<sub>1</sub> - Z<sub>2</sub></b>	<b>Hp. / kW.</b>	<b>1:1</b>	<b>M/ S</b>	<b>Piece/ Diameter</b>	<b>mm.</b>	<b>Kg.</b>	
<b>41 / 1</b>	<b>12,50 / 9,20 (a)</b>	<b>630</b>	<b>1,00</b>	<b>5 x 10</b>	<b>500 / 16,5</b>	<b>485</b>	

**a ) 1.500 / 375 Speed motor**

**Notes :** a) Driving pulley shaft diameter is Ø 64 mm.  
b) Recommended lubricant must be used otherwise the bearings and gears mounted on speed reducer will be wearen faster and the efficiency will decreased.  
c) Our company reserves the right to change or update the products without any notifications