



PRODUCED ACCORDING TO - TSE 60034

| TECHNICAL VALUES TABLE (At Nominal Weight) | | | | | | | | TSEK CERTIFICATED | | |
|--|---------------------|------|------------------|-------------------------|----------|-----------------|--------------|-------------------|--|----------------|
| MOTOR TYPE | POWER (220/380 VAC) | | PERIOD (rpm.) | CURRENTS In (Amp.) | Cos φ | EFFICIENCY η | MOMENT Nm | POLE NUMBER | ROTOR GD ² (Kg.M ²) | WEIGHT Kgr. |
| | Hp | kW | | | | | | | | |
| ÖN. 160 MC - B3 | 8,20 | 6,03 | 1.000 | 16,270 | 0,71 | 0,79 | 62,78 | 6 | 0,229 | 115 |
| ÖN. 160 LA - B3 | 10,00 | 7,35 | 1.000 | 18,651 | 0,75 | 0,81 | 77,70 | | 0,265 | 130 |
| ÖN. 160 LB - B3 | 12,50 | 9,19 | 1.000 | 22,943 | 0,75 | 0,81 | 95,94 | | 0,297 | 137 |

Notes : a) Recommended lubricant must be used otherwise the bearings mounted on electric motor shaft will be wearen faster.
b) Our company has the right to change without notification.