



PRODUCED ACCORDING TO - TSE 60034

TECHNICAL VALUES TABLE ( At Nominal Weight )								TSEK CERTIFICATED		
MOTOR TYPE	POWER ( 220/380 VAC )		PERIOD ( rpm )	CURRENTS In ( Amp. )	Cos φ	EFFICIENCY η	MOMENT Nm	POLE NUMBER	ROTOR GD <sup>2</sup> ( Kg.M <sup>2</sup> )	WEIGHT Kgr.
	Hp	kW								
ÖN. 160 MA - B3	6,20	4,56	1.500	11,23	0,85	0,72	32,86	4	0,196	105
ÖN. 160 MB - B3	7,50	5,51	1.500	14,04	0,84	0,74	40,71		0,210	110
ÖN. 160 MC - B3	8,20	6,03	1.500	14,78	0,82	0,76	42,18		0,229	115
ÖN. 160 LA - B3	10,00	7,35	1.500	17,18	0,83	0,79	51,89		0,265	130
ÖN. 160 LB - B3	12,50	9,19	1.500	20,88	0,87	0,77	65,06		0,297	145

Notes : a ) Recommended lubricant must be used otherwise the bearings mounted on electric motor shaft will be wearen faster.  
b ) Our company has the right to change without notification.