



PRODUCED ACCORDING TO - TSE 60034

TECHNICAL VALUES TABLE ( At Nominal Weight )							TSEK CERTIFICATED			
MOTOR TYPE	POWER ( 220/380 VAC )		PERIOD ( rpm. )	CURRENTS In ( Amp. )	Cos φ	EFFICIENCY η	MOMENT Nm	POLE NUMBER	ROTOR GD <sup>2</sup> ( Kg.M <sup>2</sup> )	WEIGHT Kgr.
	Hp	kW								
ÖN. 180 SA - B3	14,00	10,29	1.500	23,19	0,88	0,79	73,58	4	0,505	185
ÖN. 180 SB - B3	16,00	11,76	1.500	25,65	0,89	0,78	83,39		0,540	205
ÖN. 180 MA - B3	18,00	13,24	1.500	28,28	0,90	0,80	93,20		0,586	210
ÖN. 180 MB - B3	20,00	14,71	1.500	31,62	0,91	0,80	103,01		0,610	215
ÖN. 180 LA - B3	24,00	17,65	1.500	38,34	0,91	0,80	127,53		0,663	230
ÖN. 180 LC - B4	30,00	22,06	1.500	49,26	0,89	0,77	156,96		0,708	265

Notes : a ) Recommended lubricant must be used otherwise the bearings mounted on electric motor shaft will be wearen faster.  
b ) Our company has the right to change without notification.