

KAYRA SERİSİ (KAYRA SERIES)

MAKİNE MACHINE	MOTOR MOTOR	YÜK LOAD	MOTOR kW MOTOR kW	AKIM CURRENT	HIZ SPEED	ASKI SUSPENSION	TAHVİL RATIO	KASNAK PULLEY	H. SAYISI x ÇAP R. NUMBER x DIA.	STATİK YÜK STATIC LOAD	SEYİR MESAFESİ TRAVEL DISTANCE
KAYRA 5.5	VVVF	630 KG	5,5 kW	15 A	1 m/s	1 : 1	41 : 1	530 mm	5 x 10 mm	5000 kg	21 m
KAYRA 7.5	ÇİFT HIZ DOUBLE SPEED	500 KG	7,5kW / 1.8kW	18 A / 10 A							30 m
KAYRA 7.5	VVVF	630	7,5 kW	18 A							30 m
KAYRA 7.5	VVVF	800	7,5 kW	18 A							21 m
KAYRA 9.2	ÇİFT HIZ DOUBLE SPEED	630 KG	9,2kW / 2,3kW	23 A / 13,5 A							30 m
KAYRA 9.2	VVVF	800 KG	9,2 kW	23 A							30 m

ÖZGEN SERİSİ (OZGEN SERIES)

MAKİNE MACHINE	MOTOR MOTOR	YÜK LOAD	MOTOR kW MOTOR kW	AKIM CURRENT	HIZ SPEED	ASKI SUSPENSION	TAHVİL RATIO	KASNAK PULLEY	H. SAYISI x ÇAP R. NUMBER x DIA.	STATİK YÜK STATIC LOAD	SEYİR MESAFESİ TRAVEL DISTANCE
ÖZGEN.2	VVVF	400 KG	5,5 kW	15 A	1 m/s	1 : 1	35 : 1	450 mm	4 x 10 mm	4000 kg	30 m
ÖZGEN.2	VVVF	480 KG	6,25 kW	15,8 A							
ÖZGEN.2	ÇİFT HIZ DOUBLE SPEED	400 KG	6.25kW / 1.5kW	15,8 A / 11 A							
ÖZGEN.4	VVVF	800 KG	9,2 kW	20 A			45 : 1	560 mm	5 x 10 mm	6000 kg	30 m (*45 m)
ÖZGEN.4	VVVF	1000 KG	10,3 kW	26 A							
ÖZGEN.4	ÇİFT HIZ DOUBLE SPEED	800 KG	9,2kW / 2,3kW	20 A / 17,5 A							
ÖZGEN.4	VVVF	500	7,5 kW	17 A	1,6 m/s	53 : 2	530 mm				
ÖZGEN.4	VVVF	630	9,2 kW	20 A							
ÖZGEN.4	VVVF	800	10,3 kW	26 A							

* denge zinciri ile
* with balance chain

KLASİK SERİSİ (CLASSIC SERIES)

MAKİNE MACHINE	MOTOR MOTOR	YÜK LOAD	MOTOR kW MOTOR kW	AKIM CURRENT	HIZ SPEED	ASKI SUSPENSION	TAHVİL RATIO	KASNAK PULLEY	H. SAYISI x ÇAP R. NUMBER x DIA.	STATİK YÜK STATIC LOAD	SEYİR MESAFESİ TRAVEL DISTANCE
ÖN.160	VVVF	1000 KG	10,3 kW	26 A	1 m/s	1 : 1	44 : 1	560 mm	5 x 10 mm	6000 kg	30 m (*60 m)
ÖN.160	VVVF	630 KG	10,3 kW	26 A	1,2 m/s		44 : 2	500 mm			
ÖN.160	VVVF	630 KG	10,3 kW	26 A	1,4 m/s			560 mm			
ÖN.180	VVVF	1250 KG	14,7 kW	28 A	0,8 m/s		50 : 1	530 mm	6 x 10 mm	8000 kg	
ÖN.180	VVVF	1500 KG	17,7 kW	38 A	0,8 m/s						
ÖN.180	VVVF	3250 KG	17,7 kW	38 A	0,27 m/s		3 : 1	530 mm			
ÖN.250	VVVF	2000 KG	22 kW	50 A	0,8 m/s	1 : 1	50 : 1	570 mm	8 x 12 mm	15000 kg	
ÖN.250	VVVF	7000 KG	22 kW	50 A	0,2 m/s	4 : 1					

Daha fazla klasik seri ürünü lütfen için irtibata geçiniz.

Please contact us for more classic series product options.

* denge zinciri ile
* with balance chain

DİŞLİSİZ 160 SERİSİ (GEARLESS 160 SERIES)

MAKİNE MACHINE	MOTOR MOTOR	YÜK LOAD	MOTOR kW MOTOR kW	AKIM CURRENT	HIZ SPEED	ASKI SUSPENSION	KASNAK PULLEY	H. SAYISI x ÇAP R. NUMBER x DIA.	STATİK YÜK STATIC LOAD	SEYİR MESAFESİ TRAVEL DISTANCE
NAGEL.160-2	VVVF	400 KG	3,8 kW	8,2 A	1 m/s	2 : 1	250 mm	5 x 6.5 mm	3000 kg	24 m (* 48 m)
NAGEL.160-2	VVVF	400 KG	4,8 kW	9,7 A			320 mm	4 x 8 mm		
NAGEL.160-2	VVVF	480 KG	4,8 kW	9,7 A			250 mm	5 x 6.5 mm		
NAGEL.160-2	VVVF	480 KG	6 kW	12 A			320 mm	4 x 8 mm		
NAGEL.160-2	VVVF	400 KG	5,8 kW	8,3 A	1,6 m/s		250 mm	5 x 6.5 mm		
NAGEL.160-2	VVVF	400 KG	7,1 kW	11,5 A			320 mm	4 x 8 mm		
NAGEL.160-2	VVVF	480 KG	7,1 kW	10 A			250 mm	5 x 6.5 mm		
NAGEL.160-2	VVVF	480 KG	8,7 kW	14,5 A			320 mm	4 x 8 mm		
NAGEL.160-3	VVVF	630 KG	5,6 kW	13,8 A	1 m/s		250 mm	7 x 6.5 mm		
NAGEL.160-3	VVVF	630 KG	7 kW	18,2 A			320 mm	5 x 8 mm		
NAGEL.160-3	VVVF	800 KG	7 kW	18,2 A			250 mm	8 x 6.5 mm		
NAGEL.160-3	VVVF	800 KG	10,6 kW	22,4 A			320 mm	5 x 8 mm		
NAGEL.160-3	VVVF	630 KG	8,5 kW	14 A	1,6 m/s		250 mm	7 x 6.5 mm		
NAGEL.160-3	VVVF	630 KG	10 kW	18,3 A			320 mm	5 x 8 mm		
NAGEL.160-3	VVVF	800 KG	10 kW	18,3 A			250 mm	8 x 6.5 mm		
NAGEL.160-3	VVVF	800 KG	15 kW	26,5 A			320 mm	6 x 8 mm		
NAGEL.160-3	VVVF	480 KG	8,2 kW	15,7 A	2 m/s	250 mm	6 x 6.5 mm			
NAGEL.160-3	VVVF	480 KG	8,5 kW	20,5 A		320 mm	4 x 8 mm			
NAGEL.160-3	VVVF	630 KG	10,8 kW	20,5 A		250 mm	7 x 6.5 mm			
NAGEL.160-3	VVVF	630 KG	12 kW	27,5 A		320 mm	5 x 8 mm			

* denge zinciri ile
* with balance chain

DİŞLİSİZ 200 SERİSİ (GEARLESS 200 SERIES)

MAKİNE MACHINE	MOTOR MOTOR	YÜK LOAD	MOTOR kW MOTOR kW	AKIM CURRENT	HIZ SPEED	ASKI SUSPENSION	KASNAK PULLEY	H. SAYISI x ÇAP R. NUMBER x DIA.	STATİK YÜK STATIC LOAD	SEYİR MESAFESİ TRAVEL DISTANCE
NAGEL.200-1	VVVF	800 KG	8,4 kW	22,6 A	1 m/s	2 : 1	320 mm	5 x 8 mm	3700 kg	24 m (*48 m)
NAGEL.200-1	VVVF	1000 KG	8,4 kW	22,6 A			250 mm	8 x 6.5 mm		
NAGEL.200-1	VVVF	1000 KG	13,6 kW	34 A			320 mm	7 x 8 mm		
NAGEL.200-1	VVVF	800 KG	12,2 kW	23,5 A	1,6 m/s		320 mm	6 x 8 mm		
NAGEL.200-1	VVVF	1000 KG	12,2 kW	32,3 A			250 mm	8 x 6.5 mm		
NAGEL.200-1	VVVF	1000 KG	18,4 kW	34,8 A			320 mm	7 x 8 mm		
NAGEL.200-1	VVVF	800 KG	13,2 kW	20,5 A			2 m/s	250 mm		
NAGEL.200-1	VVVF	800 KG	13,5 kW	21,5 A	320 mm			6 x 8 mm		
NAGEL.200-2	VVVF	1000 KG	10,6 kW	26,3 A	1 m/s		320 mm	7 x 8 mm		
NAGEL.200-2	VVVF	1300 KG	10,6 kW	26,3 A			250 mm	10 x 6.5 mm		
NAGEL.200-2	VVVF	1300 KG	16,2 kW	34,8 A			320 mm	7 x 8 mm		
NAGEL.200-2	VVVF	1000 KG	15,5 kW	28,4 A	1,6 m/s		320 mm	7 x 8 mm		
NAGEL.200-2	VVVF	1300 KG	15,5 kW	28,4 A			250 mm	10 x 6.5 mm		
NAGEL.200-2	VVVF	1300 KG	22 kW	30 A			320 mm	7 x 8 mm		
NAGEL.200-2	VVVF	1000 KG	17 kW	27,5 A	2 m/s		250 mm	10 x 6.5 mm		
NAGEL.200-2	VVVF	1000 KG	17,2 kW	28,5 A			320 mm	7 x 8 mm		

* denge zinciri ile
* with balance chain